



S I T E L A Y O U T

REVISION		
NO	DATE	DESCRIPTION

- NOTES**
- This drawing is protected under the copyright act and cannot be used or reproduced in part or whole without authors consent.
  - Read only figured dimensions .
  - All construction work is to comply with the latest B .S standard codes of practice, Local Authority By-Laws and Fire regulations .
  - P.V denotes permanent ventilation and must be provided above all doors and windows where indicated or shown .
  - All walls less than 200mm thick to be reinforced with hoop iron at every alternate course .
  - Water Meter to be 300mm above G.L.
  - D.p.c denotes one layer of bituminous felt to be provided under all walls atleast 150mm above ground level .
  - All reinforced concrete works to structural engineers details and specifications.
  - Provide one row of 600 x 600 x 50mm th. pre-cast or insitu concrete paving slabs around the building as splash apron unless otherwise stated .
  - Contractors must verify all dimensions and levels on site before commencement of works . Any discrepancies must be reported to the Architect before work is put in hand .
  - All levels shown are finished levels unless otherwise stated .
  - All surface beds to be cast on well compacted and well consolidated murram or sand infill where applicably stated .
  - Depth of foundation trenches to be at a min . of 750mm below reduced ground level .
  - All pipes and services to be at a min . of 450mm below reduced ground level .

Project	
Client	
Drawing title	
job No	Owners signature
drawing No	Designer
Scale As Stated	Date Jan 2023
Drawn	Checked



